

ABOVE VIEW WALL TILE FACT SHEET



TILE BREAKDOWN

Above View wall tiles are:

- Nominally 2' x 2' wide and 1/2" thick
- 97% natural/organic materials
- Composed of gypsum, glass fiber, and other aggregates
- Weigh only 2 to 2.25 pounds per square foot
- Relief on the tiles varies from 1/4" to 3", depending on design
- Standard Factory Finish is a white latex paint (P & L Z8160, White, Soft Satin)

Due to the use of bulk enhancers, this patented composition offers these additional features:

- Stability in construction (no thin, weak spots)
- Remains true in size and plane (no warpage)
- Cuts as easily as dry wall for perimeters

Custom Tile Designs

- Available, designed by Above View or Other

CUSTOMIZATION

Custom Finishes

- Custom Color(s) available
- Faux finishing available

Custom Cutting

- Custom cutting for perimeters, both square and curved, available

FIRE CODES

Above View tiles are non-combustible. These tiles will not sustain combustion or release toxic fumes. The results of the ASTM E. 84 tunnel combustibility test performed on this product are as follows: Class A fire rating, with zero smoke spread, zero flame spread, and zero fuel contribution.

INSTALLATION REQUIREMENTS

Material shall be installed in accordance with the following recommendations: White gloves shall be worn by installers while handling **Above View** wall tiles. All boxes of tiles shall be kept in a vertical position on the job site with the arrows pointing up in order to prevent breakage. Wall Mounting instructions can be found on the next page.

PATENTS AND COPYRIGHTS

Each **Above View** ceiling tile is an exquisitely executed, copyrighted design. All tiles are manufactured using a patented composition and a proprietary manufacturing process that consistently provides a unique, high-quality product. A great deal of attention is given to the manufacturing of our tiles in order to maintain definition of details and integrity of surfaces.

WALL MOUNTING INSTRUCTIONS

MOUNTING ABOVE VIEW WALL TILES

Skrew the tile to the wall (preferable but not necessarily to studs)

Use two wood screws per tile

- longer screws around 1.5"
- Phillips, small flat heads
- larger threads (#6 - #10)

Pre – drill 2 holes, either on top or bottom or on opposite sides for counter sinking.

Start screwing with power drill. IMPORTANT, when screw is near surface switch from power drill to hand drill to countersink screws, just below surface.

Spackle to conceal screws for finished surface.

Spackle seams between tiles if desired. Sand and touch up paint if needed.