

TILE BREAKDOWN

Above View tiles are:

- Nominally 2' x 2' wide and 1/2" thick
- 97% natural/organic materials
- Composed of gypsum, glass fiber, and other aggregates
- Weigh only 2 to 2.25 pounds per square foot
- Satisfy ASTM Spec. C-635 for L/360, based on hanger wire @ 4' O.C.
- Relief on the tiles varies from 1/4" to 3", depending on design
- Standard Factory Finish is a white latex paint (P & L Z8160, White, Soft Satin)

Due to the use of bulk enhancers, this patented composition offers these additional features:

- No extra stress on the structure from excess weight
- Stability in construction (no thin, weak spots)
- Remains true in size and plane (no warpage)
- No rattling in the grid
- No need for hold-down clips
- Cuts as easily as dry wall for down lights, sprinklers, and vents

CUSTOMIZATION

Custom Ceiling Tile Designs

- Available, designed by Above View or Other

Custom Finishes

- Custom Color(s) available
- Faux finishing available

Custom Cutting And Splicing

- Custom hole cutting for lights, sprinklers and vents available
- Custom cutting for perimeters, both square and curved, available
- Custom splicing for perimeters and partial openings available

FIRE CODES

Above View tiles are non-combustible. These tiles will not sustain combustion or release toxic fumes. The results of the ASTM E. 84 tunnel combustibility test performed on this product are as follows: Class A fire rating, with zero smoke spread, zero flame spread, and zero fuel contribution.

INSTALLATION REQUIREMENTS

The tiles will drop into any standard commercial 15/16" T-Bar suspension grid, consisting of pre-punched roll-formed steel with exposed flange surface. Main runners and cross runners shall be installed to form 2' x 2' square openings. The grid shall be hung flat and level, suspended by 12 gauge pre-straightened steel wire @ 4' O.C. *We also produce tiles for 9/16" grid upon request.*

Material shall be installed in accordance with the following recommendations: White gloves shall be worn by installers while handling **Above View** ceiling tiles. All boxes of tiles shall be kept in a vertical position on the job site with the red arrow pointing up in order to prevent breakage.

PATENTS AND COPYRIGHTS

Each **Above View** ceiling tile is an exquisitely executed, copyrighted design. All tiles are manufactured using a patented composition and a proprietary manufacturing process that consistently provides a unique, high-quality product. A great deal of attention is given to the manufacturing of our tiles in order to maintain definition of details and integrity of surfaces.